



# HEA750000208-1INDT



<b>MODEL</b>		IMAC 2000
<b>Supplier</b>		THERMOBILE
<b>Heating Capacity (BTU/hr)</b>		700 000
<b>Stage</b>		1
<b>Type of combustible</b>		OIL NO1
<b>Type of heating</b>		INDIRECT
<b>Consumption (l/hr)</b>		18.9
<b>Ventilation (CFM)</b>		7,060
<b>Exterior static pressure (I.W.C.) / max. duct lenght</b>		2,6" / 200'
<b>Number of supply x Dimension</b>		1 x 24"
<b>Number of return x Dimension</b>		1 x 24"
<b>Sound Level (dB)</b>		76.5
<b>Number of filters / Dimension</b>		N/A
<b>Dimensions for 950L Tank (extra) as shown above</b>	<b>L</b>	95"
	<b>I</b>	48"
	<b>H</b>	79"
<b>Available tank (l)</b>		1000/2000/4700 (extra)
<b>Specifications - Tanks</b>		** Double Wall Structure / Transport Canada Approved / Capable of Transporting at Full Capacity **
<b>Voltage</b>		230 V - 1ph
<b>Amperage (FLA) / Main Breaker</b>		17A / 30A
<b>Approx.Weight with 950L Tank. Full / Empty (lb)</b>		4911 / 3011