



# HEA750000208-3INDT



| MODEL  |   | IMAC 2000             |
|--|---|-----------------------|
| Supplier   |   | THERMOBILE            |
| Heating Capacity (BTU/hr)                            |   | 650 000               |
| Stage  |   | 1                     |
| Type of combustible                                  |   | NATURAL GAS - PROPANE |
| Type of heating                                      |   | INDIRECT              |
| Operating combustible minimum recommended (psi)      |   | 5 à 10                |
| Type of connection for combustible                   |   | Mâle 3/4"SAE 45°      |
| Dimension of the connection                          |   | 3/4"                  |
| Consumption (ft <sup>3</sup> /hr) / (l/hr)           |   | GN 610 / P 28,89      |
| Ventilation (CFM)                                    |   | 6,500                 |
| Exterior static pressure (I.W.C.) / Max. duct length |   | 2,6" / 200'           |
| Number of supply x Dimension                         |   | 1 x 24"               |
| Number of return x Dimension                         |   | 1 x 24"               |
| Sound Level (dB)                                     |   | 76.5                  |
| Number of filters / Dimension                        |   | N/A                   |
| Dimensions   | L | 95"                   |
|  | I | 32"                   |
|  | H | 55"                   |
| Voltage  |   | 208 V - 3ph           |
| Amperage (FLA) / Main Breaker                        |   | 17A / 30A             |
| Approx. Weight (lb)                                  |   | 1300                  |