



# HEAELE150KW600C



<b>MODEL</b>		HEAELE150KW600C
<b>Supplier</b>		N/A
<b>Heating Capacity (Btu/hr)</b>		512000/307000/205000
<b>Stages</b>		150KW/90KW/60KW
<b>Type of combustible</b>		Électric
<b>Type of heating</b>		Direct
<b>Operating combustible minimum pressure (psi)</b>		Local ou à distance
<b>Type of connection</b>		Camlock/junction box
<b>Dimension of the connection</b>		16 Serie J type
<b>Consumption (ft<sup>3</sup>/hr)</b>		N/A
<b>Ventilation (cfm)</b>		6650/13100/14500 (drive)
<b>Exterior static pressure (I.W.C.)</b>		6,5"
<b>Number of supply x Dimension / Max. duct length</b>		1 x 24" / 200'
<b>Number of return x Dimension / Max. duct length</b>		1 x 24" / 12'
<b>Sound Level (dB)</b>		83/81/76
<b>Number of filters / Dimension</b>		N/A
<b>Dimensions</b>	<b>L</b>	68"
	<b>I</b>	32"
	<b>H</b>	56"
<b>Voltage</b>		575V
<b>Amperage (FLA)/ Main Breaker</b>		167A / 200A
<b>Approx. Weight (lb)</b>		950