



# HEAELE60KWF



<b>MODEL</b>	60kW	
<b>Supplier</b>	FLAGRO	
<b>Heating Capacity (BTU/hr)</b>	205 000/137 000/68 000	
<b>Stages</b>	60kW /40kW /20kW	
<b>Type of combustible</b>	ELECTRICAL	
<b>Type of heating</b>	DIRECT	
<b>Operating combustible minimum pressure (psi)</b>	N/A	
<b>Type of connection for combustible</b>	CAMLOCK/JUNCTION BOX (extra)	
<b>Thermostat</b>	REMOTE	
<b>Consumption (ft<sup>3</sup>/hr)</b>	N/A	
<b>Ventilation (CFM)</b>	3300/2800/2450	
<b>Exterior static pressure (I.W.C.)</b>	1/2"	
<b>Number of supply x Dimension / Max duct length</b>	1 x 16" / 25'	
<b>Number of return x Dimension / Max duct length</b>	1 x 16" / 12'	
<b>Sound Level (dB)</b>	71	
<b>Number of filters / Dimension</b>	1 / custom made	
<b>Dimensions</b>	<b>L</b>	48"
	<b>I</b>	25"
	<b>H</b>	32"
<b>Voltage</b>	575 3ph	
<b>Amperage(FLA)/ Main Breaker</b>	61,5A / 65A	
<b>Approx.Weight (lb)</b>	290	