



HEA1500000INDT



MODEL		I-Mac 4000
Supplier		Thermobile
Heating Capacity (BTU/hr)		1 320 000
Stage		2
Type of combustible		NATURAL GAS / PROPANE
Type of heating		INDIRECT
Operating combustible pressure recommended (psi)		5 à 10
Type of connection for combustible		1" mâle JIC 37° OU 1" FPT
Dimension of the connection		1"
Consumption (Ft³/hr) / (lb/hr)		GN 1,266 / P 59,82
Ventilation (CFM)		7 000 / 14 000
Exterior static pressure (I.W.C.)/ max duct lenght		4" / 200'
Number of supply x Dimension		2 x 24"
Number of return x Dimension		3 x 24"
Sound Level (dB)		70
Number of filters / Dimension		N/A
Dimensions	L	165"
	I	51"
	H	79"
Voltage		208-230V 3ph
Amperage (FLA) / Main Breaker		32A /40A
Approx. Weight(lb)		2866



HEA1500000INDT



MODEL		I-Mac 4000
Supplier		Thermobile
Heating Capacity (BTU/hr)		1 550 000
Stage		2
Type of combustible		OIL NO1
Type of heating		INDIRECT
Consumption (l/hr)		41.6
Ventilation (CFM)		14 000 / 7 000
Exterior static pressure (i.W.C.)/ maximum duct length		4" / 200'
Number of supply x Dimension		2 x 24"
Number of return x Dimension		3 x 24"
Sound Level (dB)		70
Number of filters / Dimension		N/A
Dimensions with tank of 1570 litres as shown above (extra)	L	165"
	I	51"
	H	101"
Tank Capacity (l)		1570
Tank Specifications		** Double Wall Structure / Transport Canada Approved / Capable of Transporting at Full Capacity **
Voltage		230 V - 3ph
Amperage (FLA) / Main Breaker		32A / 40A
Approx.Weight (lb) Full / Empty		8495 / 5355